

**Table 84.30-6
STORM BUILDING SEWER PIPE AND TUBING**

| Material | Standard |
|---|---|
| Acrylonitrile butadiene styrene (ABS) ^a | ASTM D1527; ASTM D2661; ASTM D2751; ASTM F628 |
| Acrylonitrile butadiene styrene (ABS) Composite ^a | ASTM D2680 |
| Cast iron | ASTM A74; ASTM A888; CISPI 301 |
| Concrete, circular | ASTM C14; ASTM C76 |
| Concrete, elliptical | ASTM C507/C507M |
| Copper ^b | ASTM B42; ASTM B88 |
| Polyvinyl chloride (PVC) ^a | ASTM D1785; ASTM D2665; ASTM D3034; ASTM F891 |
| PVC Corrugated Sewer Pipe with a Smooth Interior And Fittings | ASTM F949 |
| PVC Large-Diameter Plastic Gravity Sewer Pipe And Fittings | ASTM F679 |
| PVC Profile Gravity Sewer Pipe and Fittings Based On Controlled Inside Diameter | ASTM F794 |
| Type PS-46 and Type PS-115 PVC Plastic Gravity Flow Sewer Pipe And Fittings | ASTM F789 |
| Vitrified clay | ASTM C700 |

^a Thermoplastic sewer pipe shall be installed in accordance with ASTM D2321.

