



**Table 84.30-6  
STORM BUILDING SEWER PIPE AND TUBING**

<b>Material</b>	<b>Standard</b>
Acrylonitrile butadiene styrene (ABS) <sup>a</sup>	ASTM D1527; ASTM D2661; ASTM D2751; ASTM F628
Acrylonitrile butadiene styrene (ABS) Composite <sup>a</sup>	ASTM D2680
Cast iron	ASTM A74; ASTM A888; CISPI 301
Concrete, circular	ASTM C14; ASTM C76
Concrete, elliptical	ASTM C507/C507M
Copper <sup>b</sup>	ASTM B42; ASTM B88
Polyvinyl chloride (PVC) <sup>a</sup>	ASTM D1785; ASTM D2665; ASTM D3034; ASTM F891
PVC Corrugated Sewer Pipe with a Smooth Interior And Fittings	ASTM F949
PVC Large-Diameter Plastic Gravity Sewer Pipe And Fittings	ASTM F679
PVC Profile Gravity Sewer Pipe and Fittings Based On Controlled Inside Diameter	ASTM F794
Type PS-46 and Type PS-115 PVC Plastic Gravity Flow Sewer Pipe And Fittings	ASTM F789
Vitrified clay	ASTM C700

<sup>a</sup> Thermoplastic sewer pipe shall be installed in accordance with ASTM D2321.

